


This hand - held portable thermometer performs like an expensive benchtop unit. Microprocessor - based meter features easy keypad selection of measuring scale and resolution, as well as other desired operating parameters. A wide selection of standard cataloged RTD probes are available for use with this instrument when ordered with the special meter connector plug.



ADAPTERS WITH METER PLUGS



FEATURES

- Selectable Alpha (385 or 392)
- Dual LCD gives two measurements at once
- Selectable °F or °C
- Temperature Hold (up to 99 readings)
- Low Battery
- Peak Temperature Hold
- Differential Temperature
- Recall
- Field Calibration Capabilities

SPECIFICATIONS

- Accuracy:** ± 0.1% of reading, ± 0.7°F (0.4°C) (whichever is greater)
- Repeatability:** ± 0.2°F
- Range:** -330 to 1560°F (-201 to 849°C)
- Resolution:** Selectable 0.1° or 1.0° up to 999.9°
Automatic 1.0° above 999.9°
- Case:** ABS with Polycarbonate Window, Integral Tilt Stand, Rubber Feet
- Operating Ambient:** 50 to 104°F (10 to 40°C) for Stated Accuracy
- Battery:** 9 Volt Battery (200 hrs w/alkaline type)
- Size / Wt.:** 3(1/2)"W x 6(1/2)"H x 1(3/16)"D - 1 lb.

ORDERING INFORMATION

ORDER CODE	DESCRIPTION	ORDER CODE	DESCRIPTION
28 - 02200	Meter only	28 - 02240	60" mini jack coil cord (3 wire)
28 - 01810	Padded carrying case w/belt loop	28 - 02250	60" standard jack coil cord (3 wire)
28 - 02210	6" mini jack adapter (3 wire)	28 - 02230	Replacement connector
28 - 02220	6" standard jack adapter (3 wire)	PROBES	See note

Note: Standard catalog RTD probes are available for use with this instrument; however, probes must be ordered with #Z-539 connector plug option in order to be compatible with the meter input connection.